



USED ON

Part #	L (meters)	SC-Duplex, Beige		SC-Duplex, Beige	
		IL (dB)	RL (dB)	IL (dB)	RL (dB)
0-6588644-1	0.950 - 1.050	0.50	N/A	0.50	N/A
0-6588644-2	1.950 - 2.050	0.50	N/A	0.50	N/A
0-6588644-3	2.950 - 3.050	0.50	N/A	0.50	N/A
0-6588644-4	3.920 - 4.080	0.51	N/A	0.51	N/A
0-6588644-5	4.920 - 5.080	0.51	N/A	0.51	N/A
0-6588644-6	5.920 - 6.080	0.51	N/A	0.51	N/A
0-6588644-7	6.920 - 7.080	0.51	N/A	0.51	N/A
0-6588644-8	7.920 - 8.080	0.51	N/A	0.51	N/A
0-6588644-9	8.850 - 9.150	0.51	N/A	0.51	N/A
1-6588644-0	9.850 - 10.150	0.52	N/A	0.52	N/A
1-6588644-1	10.850 - 11.150	0.52	N/A	0.52	N/A
1-6588644-2	11.850 - 12.150	0.52	N/A	0.52	N/A
1-6588644-3	12.850 - 13.150	0.52	N/A	0.52	N/A
1-6588644-4	13.850 - 14.150	0.52	N/A	0.52	N/A
1-6588644-5	14.850 - 15.150	0.52	N/A	0.52	N/A
1-6588644-6	15.840 - 16.160	0.52	N/A	0.52	N/A
1-6588644-7	16.830 - 17.170	0.53	N/A	0.53	N/A
1-6588644-8	17.820 - 18.180	0.53	N/A	0.53	N/A
1-6588644-9	18.810 - 19.190	0.53	N/A	0.53	N/A
2-6588644-0	19.800 - 20.200	0.53	N/A	0.53	N/A
2-6588644-1	20.790 - 21.210	0.53	N/A	0.53	N/A
2-6588644-2	21.780 - 22.220	0.53	N/A	0.53	N/A
2-6588644-3	22.770 - 23.230	0.53	N/A	0.53	N/A
2-6588644-4	23.760 - 24.240	0.54	N/A	0.54	N/A
2-6588644-5	24.750 - 25.250	0.54	N/A	0.54	N/A
2-6588644-6	25.740 - 26.260	0.54	N/A	0.54	N/A
2-6588644-7	26.730 - 27.270	0.54	N/A	0.54	N/A
2-6588644-8	27.720 - 28.280	0.54	N/A	0.54	N/A
2-6588644-9	28.710 - 29.290	0.54	N/A	0.54	N/A
3-6588644-0	29.700 - 30.300	0.55	N/A	0.55	N/A
3-6588644-1	30.690 - 31.310	0.55	N/A	0.55	N/A
3-6588644-2	31.680 - 32.320	0.55	N/A	0.55	N/A
3-6588644-3	32.670 - 33.330	0.55	N/A	0.55	N/A
3-6588644-4	33.660 - 34.340	0.55	N/A	0.55	N/A
3-6588644-5	34.650 - 35.350	0.55	N/A	0.55	N/A
3-6588644-6	35.640 - 36.360	0.55	N/A	0.55	N/A
3-6588644-7	36.630 - 37.370	0.56	N/A	0.56	N/A
3-6588644-8	37.620 - 38.380	0.56	N/A	0.56	N/A
3-6588644-9	38.610 - 39.390	0.56	N/A	0.56	N/A
4-6588644-0	39.600 - 40.400	0.56	N/A	0.56	N/A
5-6588644-0	49.500 - 50.500	0.58	N/A	0.58	N/A
9-6588644-8	257.400 - 262.600	0.89	N/A	0.89	N/A
9-6588644-9	297.000 - 303.000	0.95	N/A	0.95	N/A


THIS DRAWING IS A CONTROLLED DOCUMENT.

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS TO BE KEPT CONFIDENTIAL AND NOT DISCLOSED TO ANY OTHER PERSONS OR ORGANIZATIONS WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC  
CE  
DIST  
16


C	Rev Per EC#	ECR-06-009980	4/26/2006	-					
P	LTR	REVISION RECORD	DATE	DN	APVD				

DIMENSIONS: meters



TOLERANCES UNLESS OTHERWISE SPECIFIED:

9 PLC	±	-
1 PLC	±	-
2 PLC	±	-
3 PLC	±	-
4 PLC	±	-

DN	Cable Assy Configurator	MATERIAL		HEAT TREAT	
OK	Cable Assy Configurator	 Tyco Electronics, Inc. Harrisburg, PA 17105-3608			
APVD	Refer to Engineering Change				
NAME	FO C/A - 2 fiber, 1.8mm, XG - 50/125, OFNP (Plenum) jacket, SC-Duplex to SC-Duplex				
SCALE	SIZE	DRAWING NO	SHEET	REV	
NTS	A2	C- 6588644	2 of 3	C	

Customer Print

D

C

B

A

Label 1

Per specification 107-1645-1



Trace # - Bar Code

Trace # - Human Readable

Part Number

Country of Origin

This label is used on all lengths on this drawing.

THIS DRAWING IS A CONTROLLED DOCUMENT.

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS NOT TO BE DISCLOSED TO ANYONE OTHER THAN TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA

LOC  
CE  
DIST  
16

C	Rev Per	ECR-06-009980	4/26/2006	-			
P	LTR	REVISION RECORD	DATE	DIN	APVD		

DIMENSIONS: meters	TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± .	1 PLC ± .
2 PLC ± .	3 PLC ± .
4 PLC ± .	

Customer Print

DIN	Cable Assy Configurator	MATERIAL	HEAT TREAT	
OK	Cable Assy Configurator			
APVD	Refer to Engineering Change	Tyco Electronics, Inc. Harrisburg, PA 17105-3608		
NAME	FO C/A - 2 fiber, 1.8mm, XG - 50/125, OFNP (Plenum) jacket, SC-Duplex to SC-Duplex			
SCALE	SIZE	DRAWING NO	SHEET	REV
NTS	A2	C- 6588644	3 of 3	C

8 7 6 5 4 3 2 1

D  
C  
B  
A