



Overview

| | |
|----------------------|--|
| Model Name | Rack ATS, 120V, 30A, L5-30P in, (16) 5-20R out |
| Includes | Mounting Hardware , Rack Mounting brackets , Serial configuration cable |
| Standard Lead Time | Usually in Stock |
| Product Distribution | Anguilla , Antigua And Barbuda , Argentina , Aruba , Bahamas , Barbados , Belize , Bermuda , Bolivia , Canada , Cayman Islands , Chile , Colombia , Costa Rica , Cuba , Dominica , Dominican Republic , Ecuador , El Salvador , Falkland Islands (Malvinas) , Grenada , Guatemala , Guyana , Haiti , Honduras , Jamaica , Mexico , Netherlands Antilles , Nicaragua , Panama , Paraguay , Peru , Puerto Rico , SAINT KITTS AND NEVIS , SAINT LUCIA , SAINT VINCENT AND THE GRENADINES , Trinidad And Tobago , United States , Uruguay , Venezuela , VIRGIN ISLANDS (UNITED STATES) |

Output

| | |
|--------------------------------------|----------------------------------|
| Nominal Output Voltage | 120V |
| Maximum Total Current Draw per Phase | 30 A |
| Output Connections | (16) NEMA 5-20R (Battery Backup) |
| Always on Outlets | 0 |
| Overload Protection | Yes |

Input

| | |
|--|-------------|
| Nominal Input Voltage | 120V |
| Input Frequency | 50/60 Hz |
| Regulatory Derated Input Current (North America) | 24 A |
| Input Connections | NEMA L5-30P |
| Cord Length | 2.44 meters |
| Number of Power Cords | 2 |
| Maximum Line Current per phase | 30 A |
| Maximum Input Current per phase | 30 A |
| Load Capacity | 0 VA |

Physical

| | |
|------------|---------|
| Net Weight | 6.33 kg |
|------------|---------|

| | |
|-----------------|----------|
| Maximum Height | 88.0 mm |
| Maximum Width | 432.0 mm |
| Maximum Depth | 236.0 mm |
| Shipping Weight | 8.82 kg |
| Shipping Height | 210.0 mm |
| Shipping Width | 584.0 mm |
| Shipping Depth | 356.0 mm |
| Color | Black |

Environmental

| | |
|-----------------------------|----------------|
| Operating Environment | -5 - 45 °C |
| Operating Relative Humidity | 5 - 95 % |
| Operating Elevation | 0-3000 meters |
| Storage Temperature | -25 - 65 °C |
| Storage Relative Humidity | 5 - 95 % |
| Storage Elevation | 0-15000 meters |

Conformance

| | |
|-------------------|--|
| Approvals | EN 55022 Class A , FCC Part 15 Class A |
| Standard warranty | 2 years repair or replace |