

Clarity 6 angled 24-port Category 6 patch panel, high density, six-port modules, 19" x 1.75"

OR-PHA66U24



Clarity⁶ angled 24-port Category 6 patch panel, high density, six-port modules, 19" x 1.75".

features & benefits



- Recessed design with lower mounted profile
- ETL verified to TIA Category 6 component spec
- Center tuned to Clarity⁶ patch cords
- Universally wired 110 termination
- New IDC housing
- Supplied rear cable management
- High density design
- RoHS compliant

specifications

General Info

Mod Jack Wiring: Universal T568A/B
Number Of Ports: 24

Listing Agencies/Third Party Information

CUL Listing No: E131600
ETL Listing No: 3013270-004
ETL Standard: Yes
FCC Standard: Yes
UL Listing No: E131600
UL Standard: Yes

Construction Information

Component1: Panel

Component2: Six-port jack housing

Component3: Six-port rear IDC housing

Component4: Array of eight modular dual reactance Category 6 contacts

Component5: IDC contacts (low noise)

Finish Plating1: Painted black texture with blue silkscreen

Finish Plating4: Nickel plating and a minimum of 50 micro inches of selective gold plating in contact area

Finish Plating5: Nickel plating with tin over plate

Material1: .090" Aluminum

Material2: High impact thermoplastic UL 94V-0

Material3: Polycarbonate

Material4: Beryllium Copper

Material5: Phosphor Bronze

Dimensions

Cable Diameter Range: 22-26 AWG

Depth Metric: 46.23 mm

Height Metric: 44.45 mm

Height U S: 1.75"

Width Metric: 482.6 mm

Technical Information

Category Rating: Category 6

Performance Rating: Category 6

Buy American Act Compliance

Country of Origin: MEXICO

Buy American Act Status: Trade Agreement Act Compliant